



序号	名称	材质	数量
1	接地插销	黄铜t2.0	1
2	载流插销	黄铜t2.0	2
3	保险管	PA66	1
4	基座	PA66	1
5	快接端子	黄铜t0.8	3
6	铆钉	黄铜t2.0	2
7	保险夹	磷铜t0.5	2
8	连接片	黄铜t0.5	1

Rating : 10A 250V AC KC TUV 3C CE
 Fuse : 250VAC 6.3A 2.5W
 Insert And Extract Force: 1.36kgf~6.8kgf
 Terminal Strength: $\geq 80N$
 Operating Life: ≥ 5000 cycles
 Withstand Voltage: Between all
 terminals: 2500VAC (50-60Hz) 1min
 terminals to Base: 3750V AC (50-60Hz) 1min
 Leakage Current : 1mA
 Insulation Resistance: $\geq 100M\Omega$ 500V DC

A4				普通公差	乐清市朗正电子有限公司 YUEQING LANZ ELECTRONICS CO., LTD								
A3				COMMON TOLERANCE :									
A2				UP TO 5	± 0.20	单位	mm	投影		品名	Ac Inlet C14型	比例	Free
A1				ABOVE 5 TO 30	± 0.30	UNIT		PROJECTED		料号		SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	绘图	吴瑜	核对		MODEL NO.	LZ-14-F5-S		
						日期	2020. 11. 14	核准		图号	LANZ/CRS-LZ14F5S		
						DATE		APPROVAL BY		DWG NO.			