



NOTES:

1. Rating:
CQC CE 16A 250V AC
20A 125V AC
2. Circuit Diagram: 4P ON-OFF
3. Terminal Strength: $\geq 80N$
4. Electrical life: ≥ 10000 cycles
5. Withstand Voltage: Withstand Voltage: 1500VAC 1min
Terminals to Button: 3000VAC 1min
Leakage Current: 1mA
6. Current resistance: $\leq 50m\Omega$ (initial)
7. Insulation resistance: $\geq 100M\Omega$
8. Body Material: NYLON 66 94V-0²
9. Operating Force: 4N-8N

Rating :

16A 250V AC 3C TUV CE KC
20A 250V AC UL cUL

Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
terminals to Base: 3750V AC (50-60Hz) 1min
Leakage Current : 1mA

Insulation Resistance: $\geq 100M\Omega$ 500V DC

Body Material: NYLON 66 94V-0

Glow-wire temp: 750°C

A4														
A3					COMMON TOLERANCE :									
A2					UP TO 5	± 0.20	UNIT	mm	PROJECTED		PRODUCT NAME	Ac Inlet C14	SCALE	Free
A1					ABOVE 5 TO 30	± 0.30	DRAWN BY	WU YU	CHECKED BY		MODEL NO.	LZ-102S-(KCD4+20-2)		
REV.	DATE	REVISION	DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	DATE	2021. 5. 14	APPROVAL BY		DWG NO.	LANZ/CRS-LZ102SKCD4202		



YUEQING LANZ Electronics Co., Ltd