



PANEL CUT-OUT		
Z	Y	X
0.8~1	72.4~72.5	34.6~34.7
1.~1.5	72.4~72.5	35.6~35.7
1.8~2.2	72.4~72.5	36.4~36.5

PANEL CUT-OUT

- NOTES:
- Rating:
CQC CE 16A 250V AC
20A 125V AC
 - Circuit Diagram:4P ON-OFF
 - Terminal Strength: $\geq 80N$
 - Electrical life: ≥ 10000 cycles
 - Withstand Voltage:Withstand Voltage:1500VAC 1min
Terminals to Button:3000VAC 1min
Leakage Current:1mA
 - Current resistance: $\leq 50m\Omega$ (initial)
 - Insulation resistance: $\geq 100M\Omega$
 - Body Materil:NYLON 66 94V-0²
 - Operating Force:4N-8N

Rating :
10A 250V AC 3C TUV CE KC
Fuse : 250V AC 6.3A 2.5W
Withstand Voltage:Between all terminals:2500VAC (50-60Hz)1min
terminals to Base:3750V AC (50-60Hz)1min
Leakage Current : 1mA
Insulation Resistance: $\geq 100M\Omega$ 500V DC
Body Materil:NYLON 66 94V-0
Glow-wire tep: 750°C

A4													
A3				COMMON TOLERANCE :									
A2				UP TO 5	± 0.20	UNIT	mm	PROJECTED		PRODUCT NAME	Ac Inlet C14	SCALE	Free
A1				ABOVE 5 TO 30	± 0.30	DRAWN BY	WU YU	CHECKED BY		MODEL NO.	LZ-103		
REV.	DATE	REVISION	DESCRIPTION	ISSUE	ANGULAR	DATE	2021. 5. 14	APPROVAL BY		DWG NO.	LANZ/CRS-LZ103		



YUEQING LANZ Electronics Co., Ltd