



PANEL CUT-OUT

NOTES:  
 1. Rating:  
 CQC CE 16A 250V AC  
 20A 125V AC  
 2. Circuit Diagram: 4P ON-OFF  
 3. Terminal Strength:  $\geq 80N$   
 4. Electrical life:  $\geq 10000$  cycles  
 5. Withstand Voltage: Withstand Voltage: 1500VAC 1min  
 Terminals to Button: 3000VAC 1min  
 Leakage Current: 1mA  
 6. Current resistance:  $\leq 50m\Omega$  (initial)  
 7. Insulation resistance:  $\geq 100M\Omega$   
 8. Body Materil: NYLON 66 94V-0<sup>2</sup>  
 9. Operating Force: 4N-8N

Rating :  
 10A 250V AC 3C TUV CE KC  
 Fuse : 250V AC 6.3A 2.5W  
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min  
 terminals to Base: 3750V AC (50-60Hz) 1min  
 Leakage Current : 1mA  
 Insulation Resistance:  $\geq 100M\Omega$  500V DC  
 Body Materil: NYLON 66 94V-0  
 Glow-wire tep: 750°C

A4													
A3													
A2													
A1													
REV.	DATE	REVISION	DESCRIPTION	ISSUE									

COMMON TOLERANCE :

UP TO 5	$\pm 0.20$
ABOVE 5 TO 30	$\pm 0.30$
ABOVE 30	$\pm 0.50$
ANGULAR	$\pm 5^\circ$



YUEQING LANZ Electronics Co., Ltd

UNIT	mm	PROJECTED		PRODUCT NAME	Ac Inlet C14	SCALE	Free
DRAWN BY	WU YU	CHECKED BY		MODEL NO.	LZ-103S		
DATE	2021. 5. 14	APPROVAL BY		DWG NO.	LANZ/CRS-LZ103S		